



No.	QTY.	DESCRIPTION	MATERIAL
1	1	STEM	LOW LEAD BRASS ALLOY
2	2	O-RING	EPDM ASTM D2000
3	1	BALL	LOW LEAD BRASS ALLOY
4	1	GASKET - SEAL	NITRILE ASTM D2000
5	1	BODY	CAST LOW LEAD BRASS ALLOY
6	1	O-RING	EPDM ASTM D2000
7	1	END PIECE	CAST LOW LEAD BRASS ALLOY
8	1	CAP	CAST BRASS ASTM B62 ALLOY C83600
9	1	SOLID PIN	AISI 303 STAINLESS STEEL
10	1	SADDLE NUT	CAST BRASS ASTM B62 ALLOY C83600
11	1	SNAP RING	COPPER ALLOY CDA521
12	1	RUBBER GASKET	NITRILE ASTM D2000
13	1	PJ GASKET	BUNA-N ASTM D2000
14	1	PJ WASHER	POLYPROPYLENE
15	1	CLPG NUT SUB	CAST BRASS ASTM B62 ALLOY C83600

SIZE	øA	B	C	D	E
5/8x3/4R	.625	1.688	1.719	2.120	3.839
5/8x3/4	.625	1.696	1.719	2.323	4.042
5/8x3/4x3/4R	.750	1.688	1.719	2.120	3.839
5/8x3/4x3/4	.750	1.696	1.719	2.323	4.042
5/8x3/4x1	.750	1.696	2.125	2.323	4.448
1R	1.000	1.952	2.125	2.323	4.448
1	1.000	1.952	2.125	2.617	4.742

FILEPATH: PROD-ENG\MUELLER\APPROVED\P24258N

DRFTR	RWB	5/27/10					
CHKR							
ENGR							
MGR							
			UNLESS OTHERWISE NOTED	THIRD ANGLE PROJECTION			
			SURFACE PREPARATION:				
			BREAK CORNER(S) ---- .000				
			SURFACE FINISH -- XX RMS	REF. No.			
			TOLERANCE(S):	SCALE			
			LINEAR ----- ± .000	NONE			
			ANGULAR ----- ± 0°00'				
			STK No:				
			MAT'L:				
			DESCR.	PART NUMBER			
REV	ECR	DESCRIPTION	DATE	BY	CHKR	MUELLER ANGLE METER BALL VALVE	P24258N
						LOW LEAD BRASS ("PJ CTS" x MTR)	
PER EST NO: DXXXX EST FIN WT = 0.0000 lbs							

PART NUMBER  
P24258N  
MRKTG