



No.	DESCRIPTION	MATERIAL
1	STEM	LOW LEAD BRASS ALLOY
2	O-RING	EPDM D2000
3	BALL	LOW LEAD BRASS ALLOY
4	GASKET - SEAL	NITRILE D2000
5	BODY	LOW LEAD BRASS ALLOY
6	O-RING	EPDM D2000
7	END PIECE	LOW LEAD BRASS ALLOY
8	CAP	CAST BRASS ASTM B62 ALLOY C83600
9	SOLID PIN	AISI 303 STAINLESS STEEL
10	TUBE NUT	CAST BRASS ASTM B62 ALLOY C83600
11	LOCK NUT	CAST BRASS ASTM B62 ALLOY C83600
12	RUBBER GASKET	NITRILE D2000

SIZE	ØA	B	C	D	E
5/8x3/4R	.625	1.828	1.984	2.120	4.104
5/8x3/4	.750	1.828	1.984	2.327	4.311
5/8x1	.750	1.828	2.359	2.327	4.686
5/8x3/4x3/4R	.625	1.828	1.984	2.120	4.104
5/8x3/4x3/4	.750	1.828	1.984	2.323	4.307
5/8x3/4x1	.750	1.828	2.359	2.323	4.682
1R	.750	1.953	2.359	2.323	4.682
1	1.000	2.330	2.359	2.617	4.976

NOTE: ALL WETTED PARTS ARE LOW LEAD BRASS ALLOY

FILEPATH: PROD-ENG\MUELLER\ASYSUBMITTALS\B24264N

DRFTR	JGarvin	6/11/10	Mueller Co.		
CHKR					
ENGR					
MGR					
			UNLESS OTHERWISE NOTED	THIRD ANGLE PROJECTION	
			SURFACE PREPARATION:		
			BREAK CORNER(S) ---- .000		
			SURFACE FINISH -- XX RMS	REF. No.	
			TOLERANCE(S):	SCALE	
			LINEAR ----- ± .000	NONE	
			ANGULAR ----- ± 0°00'		
			STK No:		
			MAT'L:		
			DESCR.		
			BALL ANGLE METER VALVE	PART NUMBER	
			LOW LED BRASS (CS x IRON BAR)	B24264N	
REV	ECR	DESCRIPTION	DATE	BY	CHKR
PER EST NO: DXXXX EST FIN WT = 0.0000 lbs					

TITLE TO AND OWNERSHIP OF THIS ENGINEERING DATA REMAINS IN Mueller Co. NO USE IS TO BE MADE OF THIS DATA EXCEPT AS SPECIFICALLY AUTHORIZED BY Mueller Co. ASSENT ON THE PART OF THE RECIPIENT TO THESE CONDITIONS IS PRESUMED.

PART NUMBER
B24264N
442-MRKTNG