



No.	DESCRIPTION	MATERIAL
1	STEM	LOW LEAD BRASS ALLOY
2	O-RING	EPDM D2000
3	BALL	LOW LEAD BRASS ALLOY
4	GASKET - SEAL	NITRILE D2000
5	BODY	CAST LOW LEAD BRASS ALLOY
6	O-RING	EPDM D2000
7	END PIECE	CAST LOW LEAD BRASS ALLOY
8	CAP	CAST BRASS ASTM B62 ALLOY C83600
9	SOLID PIN	AISI 303 STAINLESS STEEL
10	SADDLE NUT	CAST BRASS ASTM B62 ALLOY C83600
11	RUBBER GASKET	NITRILE D2000

SIZE	ØA	B	C	D	E
5/8x3/4R	.625	1.140	1.656	2.120	3.776
5/8x3/4	.625	1.140	1.656	2.327	3.983
5/8x3/4x3/4R	.720	1.140	1.656	2.120	3.776
5/8x3/4x3/4	.720	1.140	2.125	2.323	4.448
1R	.750	1.140	2.031	2.323	4.354
1	1.000	1.455	2.031	2.617	4.648

NOTE: ALL WETTED PARTS ARE LOW LEAD BRASS ALLOY

FILEPATH: PROD-ENG\MUELLER\ASYSUBMITTALS\B24278N

						DRFTR	RWB	7/16/13			
						CHKR					
						ENGR					
						MGR					
									UNLESS OTHERWISE NOTED	THIRD ANGLE PROJECTION	
									SURFACE PREPARATION:		
									BREAK CORNER(S) ---- .000		
									SURFACE FINISH -- XX RMS	REF. No.	SCALE
									TOLERANCE(S):		NONE
									LINEAR ----- ± .000		
									ANGULAR ----- ± 0°00'		
									STK No:		
									MAT'L:		
									DESCR.	BALL LLB ANGLE METER VALVE (FIP x IB)	DWG NUMBER B24278N
									PER EST NO: DXXXX	EST FIN WT = 0.0000 lbs	

DWG NUMBER
B24278N
442-MRKTNG

TITLE TO AND OWNERSHIP OF THIS ENGINEERING DATA REMAINS IN Mueller Co. NO USE IS TO BE MADE OF THIS DATA EXCEPT AS SPECIFICALLY AUTHORIZED BY Mueller Co. ASSENT ON THE PART OF THE RECIPIENT TO THESE CONDITIONS IS PRESUMED