

MATERIAL SAFETY DATA SHEET

F63RL15
01 00

DATE OF PREPARATION
Nov 28, 2009

SECTION 1 — PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NUMBER

F63RL15

PRODUCT NAME

POLANE® SP Polyurethane Enamel (Part A), Mueller Red

MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY
101 Prospect Avenue N.W.
Cleveland, OH 44115

Telephone Numbers and Websites

| | |
|----------------------------------------------------------------------------------------|----------------|
| Regulatory Information | (216) 566-2902 |
| Medical Emergency | (216) 566-2917 |
| Transportation Emergency* | (800) 424-9300 |
| <small>*for Chemical Emergency ONLY (spill, leak, fire, exposure, or accident)</small> | |

SECTION 2 — COMPOSITION/INFORMATION ON INGREDIENTS

| % by Weight | CAS Number | Ingredient | Units | Vapor Pressure |
|-------------|------------|-------------------------------------|-----------------------------|----------------|
| 23 | 110-43-0 | Methyl n-Amyl Ketone | | |
| | | ACGIH TLV | 50 PPM | 3.855 mm |
| | | OSHA PEL | 100 PPM | |
| 10 | 123-86-4 | n-Butyl Acetate | | |
| | | ACGIH TLV | 150 PPM | 10 mm |
| | | ACGIH TLV | 200 PPM STEL | |
| | | OSHA PEL | 150 PPM | |
| | | OSHA PEL | 200 PPM STEL | |
| 1 | 108-65-6 | 1-Methoxy-2-Propanol Acetate | | |
| | | ACGIH TLV | Not Available | 1.8 mm |
| | | OSHA PEL | Not Available | |
| 2 | 13463-67-7 | Titanium Dioxide | | |
| | | ACGIH TLV | 10 mg/m3 as Dust | |
| | | OSHA PEL | 15 mg/m3 Total Dust | |
| | | OSHA PEL | 5 mg/m3 Respirable Fraction | |

SECTION 3 — HAZARDS IDENTIFICATION

ROUTES OF EXPOSURE

INHALATION of vapor or spray mist.
EYE or SKIN contact with the product, vapor or spray mist.

EFFECTS OF OVEREXPOSURE

EYES: Irritation.
SKIN: Prolonged or repeated exposure may cause irritation.
INHALATION: Irritation of the upper respiratory system.

HMIS Codes

| | |
|---------------------|----|
| Health | 2* |
| Flammability | 3 |
| Reactivity | 0 |

May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.
Prolonged overexposure to solvent ingredients in Section 2 may cause adverse effects to the liver, urinary and blood forming systems.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.
Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

May cause allergic respiratory and/or skin reaction in susceptible persons or sensitization. This effect may be delayed several hours after exposure.
Persons sensitive to isocyanates will experience increased allergic reaction on repeated exposure.

CANCER INFORMATION

For complete discussion of toxicology data refer to Section 11.

830001473

SECTION 4 — FIRST AID MEASURES

- EYES:** Flush eyes with large amounts of water for 15 minutes. Get medical attention.
- SKIN:** Wash affected area thoroughly with soap and water.
Remove contaminated clothing and launder before re-use.
- INHALATION:** If any breathing problems occur during use, **LEAVE THE AREA** and get fresh air. If problems remain or occur later, **IMMEDIATELY** get medical attention.
- INGESTION:** Do not induce vomiting. Get medical attention immediately.

SECTION 5 — FIRE FIGHTING MEASURES

| | | | |
|----------------------------------|-------------------|--------------------|------------------------------------------------------------------------------------------|
| FLASH POINT 80 °F PMCC | LEL 0.9 | UEL 13.1 | FLAMMABILITY CLASSIFICATION RED LABEL -- Flammable, Flash below 100 °F (38 °C) |
|----------------------------------|-------------------|--------------------|------------------------------------------------------------------------------------------|

EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode when exposed to extreme heat.

Application to hot surfaces requires special precautions.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

SECTION 6 — ACCIDENTAL RELEASE MEASURES**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

- Remove all sources of ignition. Ventilate the area.
- Remove with inert absorbent.

SECTION 7 — HANDLING AND STORAGE**STORAGE CATEGORY**

DOL Storage Class IC

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGEContents are **FLAMMABLE**. Keep away from heat, sparks, and open flame.

During use and until all vapors are gone: Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition.

Consult NFPA Code. Use approved Bonding and Grounding procedures.

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

SECTION 8 — EXPOSURE CONTROLS/PERSONAL PROTECTION**PRECAUTIONS TO BE TAKEN IN USE****NO PERSON SHOULD USE THIS PRODUCT, OR BE IN THE AREA WHERE IT IS BEING USED, IF THEY HAVE CHRONIC (LONG-TERM) LUNG OR BREATHING PROBLEMS OR IF THEY EVER HAD A REACTION TO ISOCYANATES.**

Use only with adequate ventilation.

Avoid contact with skin and eyes. Avoid breathing vapor and spray mist.

Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m³ (total dust), 3 mg/m³ (respirable fraction), OSHA PEL 15 mg/m³ (total dust), 5 mg/m³ (respirable fraction).**VENTILATION**

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits.

Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTIONWhere overspray is present, a positive pressure air supplied respirator (TC19C NIOSH/MSHA approved) should be worn. If unavailable, a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2 may be effective. Follow respirator manufacturers directions for use. Wear the respirator for the whole time of spraying and until all vapors and mists are gone. **NO PERSONS SHOULD BE ALLOWED IN THE AREA WHERE THIS PRODUCT IS BEING USED UNLESS EQUIPPED WITH THE SAME RESPIRATOR PROTECTION RECOMMENDED FOR THE PAINTERS.**

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

PROTECTIVE GLOVES

To prevent skin contact, wear gloves which are recommended by glove supplier for protection against materials in Section 2.

830001473

EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

OTHER PROTECTIVE EQUIPMENT

Use barrier cream on exposed skin.

OTHER PRECAUTIONS

This product must be mixed with other components before use. Before opening the packages, READ AND FOLLOW WARNING LABELS ON ALL COMPONENTS.

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES

| | | |
|-------------------------------------------------------------------|-------------------|------------------------------------------|
| PRODUCT WEIGHT | 8.72 lb/gal | 1045 g/l |
| SPECIFIC GRAVITY | 1.05 | |
| BOILING POINT | 255 - 419 °F | 123 - 215 °C |
| MELTING POINT | Not Available | |
| VOLATILE VOLUME | 45% | |
| EVAPORATION RATE | Slower than ether | |
| VAPOR DENSITY | Heavier than air | |
| SOLUBILITY IN WATER | N.A. | |
| VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged) | | |
| 3.24lb/gal | 388g/l | Less Water and Federally Exempt Solvents |
| 3.24lb/gal | 388g/l | Emitted VOC |

SECTION 10 — STABILITY AND REACTIVITY

STABILITY — Stable

CONDITIONS TO AVOID

None known.

INCOMPATIBILITY

None known.

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide, Hydrogen Chloride

HAZARDOUS POLYMERIZATION

Will not occur

SECTION 11 — TOXICOLOGICAL INFORMATION

CHRONIC HEALTH HAZARDS

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

IARC's Monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to titanium dioxide but inadequate evidence for carcinogenicity in humans and has assigned a Group 2B rating. In addition, the IARC summary concludes, "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium is bound to other materials, such as paint."

TOXICOLOGY DATA

| CAS No. | Ingredient Name | | | |
|------------|------------------------------|----------|-----|---------------|
| 110-43-0 | Methyl n-Amyl Ketone | LC50 RAT | 4HR | Not Available |
| | | LD50 RAT | | 1670 mg/kg |
| 123-86-4 | n-Butyl Acetate | LC50 RAT | 4HR | 2000 ppm |
| | | LD50 RAT | | 13100 mg/kg |
| 108-65-6 | 1-Methoxy-2-Propanol Acetate | LC50 RAT | 4HR | Not Available |
| | | LD50 RAT | | 8500 mg/kg |
| 13463-67-7 | Titanium Dioxide | LC50 RAT | 4HR | Not Available |
| | | LD50 RAT | | Not Available |

SECTION 12 — ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

No data available.

SECTION 13 — DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

83000/473

Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers. Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

SECTION 14 — TRANSPORT INFORMATION

US Ground (DOT)

1 Gallon and Less may be Classed as CONSUMER COMMODITY, ORM-D

Larger Containers are Regulated as:
UN1263, PAINT, 3, PG III, (ERG#128)

Bulk Containers may be Shipped as:

UN1263, PAINT, 3, PG III, (ERG#128)

Canada (TDG)

UN1263, PAINT, CLASS 3, PG III, LIMITED QUANTITY, (ERG#128)

IMO

UN1263, PAINT, CLASS 3, PG III, (27 C c.c.), EmS F-E, S-E

SECTION 15 — REGULATORY INFORMATION

SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

| CAS No. | CHEMICAL/COMPOUND | % by WT | % Element |
|---------|-------------------|---------|-----------|
|---------|-------------------|---------|-----------|

No ingredients in this product are subject to SARA 313 (40 CFR 372.65C) Supplier Notification.

CALIFORNIA PROPOSITION 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

SECTION 16 — OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

83000/473

Air Quality Data Sheet

Jun 25, 2009

01 00X
Product Number
HL1468F63

THE SHERWIN-WILLIAMS COMPANY
101 Prospect Avenue N.W.
Cleveland, OH 44115

PRODUCT NAME
POLANE SP MUELLER RED

The composition given below is the composition of the product AS FORMULATED. Variations may occur on individual batches because of adjustments made during production.

Weight/Gallon Product
8.73 lbs/gallon

VOC (LESS EXEMPT SOLVENTS)
388 grams/l
3.24 lb/gal

Non-Volatile
Weight 62.9%
Volume 54.0%

Volatile
Weight 37.1%
Volume 46.0%

Density of Organic Solvent Blend
7.05 Pounds/Gallon

Solvent Composition

| CAS No. | Ingredient | Percent of Volatile | |
|------------|-------------------------------|---------------------|-----------|
| | | by Weight | by Volume |
| 1330-20-7 | Xylene | 0.5 | 0.5 |
| 34590-94-8 | 2-Methoxymethylethoxypropanol | 0.5 | 0.4 |
| 110-43-0 | Methyl n-Amyl Ketone | 61.4 | 64.2 |
| 80-62-6 | Methyl Methacrylate | 0.3 | 0.3 |
| 123-86-4 | n-Butyl Acetate | 27.5 | 26.5 |
| 868-77-9 | 2-Hydroxyethyl Methacrylate | 0.3 | 0.2 |
| 97-88-1 | Butyl Methacrylate | 0.4 | 0.4 |
| 108-65-6 | 1-Methoxy-2-Propanol Acetate | 3.1 | 2.7 |
| 106-65-0 | Dimethyl Succinate | 1.7 | 1.3 |
| 1119-40-0 | Dimethyl Glutarate | 3.9 | 3.0 |

Solvent Blend Composition Per Classification

| | |
|-----------------------------------------------------------------------|-----|
| Olefins or Cyclo-Olefinic compounds | 0.9 |
| Aromatic Hydrocarbons with 8 or more Carbon Atoms except Ethylbenzene | 0.5 |
| Branched Ketones | 0.0 |
| Ethylbenzene and/or Toluene and/or Trichloroethylene | 0.1 |
| Total Non-Complying | 1.5 |

The Solvent Blend of this product IS NOT PHOTOCHEMICAL as packaged.

830001473