

MUELLER® M98™ Top Entry Dual Check Valve

Convenient Top-entry Design



ASSE Certified/Easy in-line access

The Mueller® Top Entry Dual Check Valve offers protection from backflow at the water service entrance. This compact unit is designed for installation at the water meter outlet, providing easy access to the poppets with the valve in line.

Dual modular poppets made of acetyl resin with stainless steel springs and elastomeric seals assure reliable operation without chattering, vibration or causing water hammer. The O-ring sealed poppets are press fit into the body and retained by an acetyl resin spacer which is locked in place so it cannot move or restrict flow. The top-entry design allows easy access and removal of the poppets for field or shop testing.



Features:

- Complies with ASSE Standard 1024
- Corrosion-resistant materials
- Fully independent plastic check modules
- 175 psig pressure, 180°F ratings
- Meets applicable AWWA 800 requirements
- Excellent flow characteristics

Inlet/Outlet Combinations:

Inlet may be:

- Meter Swivel Nut (5/8", 5/8"x3/4"-3/4", 1" Meter)
- Meter Flange (1-1/2", 2" Meter)
- Iron Meter Bar Lock Nut (5/8", 5/8"x3/4"-3/4", 1" Meter)

Outlet may be:

- Mueller 110® Compression Connection (CTS) (3/4", 1", 2")
- Mueller Pack Joint Connection (CTS) (3/4", 1")
- FIP (3/4", 1", 1-1/2", 2")
- MIP (3/4", 1")
- Copper Flare (3/4", 1")

Options:

- Test Drain Valve (top mounted)
- Plain Meter Swivel Nut (without Saddle feature)

Materials:

Body - Bronze, ASTM B584 Alloy C89833

Check Valve Modules - injection molded acetyl resin

Springs - stainless steel


Seals/O-rings - EPDM

Standards:

- Tested and certified to meet or exceed the requirements of ANSI/ASSE Standard 1024
- CSA Certified to Standard B645.6
- Complies with AWWA800.

Pressure/Temperature:

- 175 psig maximum working pressure
- 180°F maximum working temperature



Dimensions			
Size	A	B	C
3/4"	1-15/16"	5-11/16"	4-3/32"
1"	2-21/64"	6-16/32"	4-17/32"
1-1/2" / 2"	2-3/16"	10-1/32"	7-1/2"

*2" meter flange is double drilled to accept 1-1/2" and 2" meters.
** 3/4" inlet/1" outlet combination available – not ASSE approved.

Mueller Co.

Smart Move™

Mueller Co.

Customer Service - Decatur, IL
Water Division: 1.800.423.1323
www.muellercompany.com

moreinfo@muellercompany.com
Mueller Canada Inc. - Barrie, Ontario
Canada: 1.705.719.9965

Copyright © 2014 Mueller Co., LLC. All Rights Reserved.

The trademarks, logos and service marks displayed in this document herein are the property of Mueller Co., LLC, its affiliates or other third parties. Products above marked with a section symbol (§) are subject to patents or patent applications. For details, visit www.mwppat.com. These products are intended for use in potable water applications. Please contact your Mueller Sales or Customer Service Representative concerning any other application(s).

Form 12072 - Rev 10/14