



CATALOG#	DESCRIPTION	Material	QTY.
1	OPERATING NUT	MAGANESE BRONZE	1
2-1	BONNET & HOUSING COVER O-RING 223	RUBBER	2
2-1A	WIPER RING	RUBBER	2
2-2	STEM SEAL O-RING	RUBBER	2
3	LUBRICATING SCREW	STAINLESS STEEL	1
4-1	THRUST BEARING	PLASTIC	1
7-5	4.5" OPEN LEFT BONNET	CAST IRON	1
9-1	BEARING HOUSING COVER	CAST IRON	1
14	BEARING HOUSING GASKET	FIBER BOARD	1
15-2	BEARING HOUSING	CAST IRON	1
15-2A	UPPER ROD SLEEVE	PLASTIC	1
15-2B	ROD SLEEVE OUTSIDE O-RING	RUBBER	2
16-2	HOUSING COVER SCREW CAP	STEEL	4
16-3	HOUSING COVER CAP SCREW LONG	STEEL	4
	HOUSING COVER CAP SCREW SHORT	STEEL	2
18-9	CENTURY UPPER BARREL	CAST IRON	1
18-10-1	BARREL PIPE	DUCTILE IRON PIPE	1
18-10-2	HYDRANT BARREL FLANGE	DUCTILE IRON	1
18-10-2T	TRAFFIC FLANGE	CAST IRON	1
18-10-3	FLANGE SIDE BOLT, GROUND LINE	STAINLESS STEEL	2
18-10-3A	FLANGE SIDE NUT, GROUND LINE	STAINLESS STEEL	2
18-10-3B	FLANGE SIDE BOLT, BELOW GROUND	STAINLESS STEEL	2
18-10-3C	FLANGE SIDE NUT, BELOW GROUND	STAINLESS STEEL	2
20-1	HOSE NOZZLE	BRASS	2
20-2	HOSE NOZZLE RETAINING RING	STEEL	2
20-3	HYDRANT NOZZLE GASKET	RUBBER	2
21-1	HOSE CAP	CAST IRON	2
22	HOSE NOZZLE CAP GASKET	RUBBER	2
25-3	100MM STORZ PUMPER NOZZLE	BRASS	1
25-4	PUMPER NOZZLE RETAINER	BRONZE	1
25-5	PUMPER NOZZLE O-RING	RUBBER	1
26-1	100MM STORZ PUMPER CAP	CAST IRON	1
27	PUMPER CAP O-RING	RUBBER	1
30-5-1	UPPER ROD	HOT ROLLED STEEL	1
30-6	LOWER ROD	HOT ROLLED STEEL	1
30-51 T	BREAKABLE ROD COUPLING	CAST IRON	1
30-51-1	ROD GUIDE	DUCTILE IRON	1
30-51-1A	ROD GUIDE SET SCREW	STEEL	1
30-51-2A	COUPLING COTTER PIN	STAINLESS STEEL	2
30-51-2T	COUPLING CLEVIS PIN	COLD ROLLED STEEL	2
31	DRIP LEVER	BRONZE	1
32	DRIP LEVER COTTER PIN	BRASS	3
33-1	DRIP LEVER WASHER	PLASTIC	3
33-1A	DRIP WASHER RETAINER/HEX NUT	BRASS	3
33-1B	NON-DRAINING TUBE	BRASS	3
35	4.5" HYDRANT SEAT	BRASS	1
36	SEAT GASKET	RUBBER	1
37	Ø4.50" DRAIN RING	BRONZE	1
38	BARREL AND BASE GASKET	RUBBER	3
39-6	BASE FLANGE BOLT	STAINLESS STEEL	8
39-6A	BASE FLANGE NUT	STAINLESS STEEL	8
39-10	GROUND FLANGE BOLT	CARBON STEEL	8
39-10A	GROUND FLANGE NUT	STEEL	8
40-2	VALVE BALL TOP Ø4.5"	CAST IRON	1
41	HYDRANT VALVE BALL	RUBBER	1
42-2	VALVE BALL BOTTOM	CAST IRON	1
43-1	VALVE SLEEVE	PLASTIC	1
43-2	VALVE SLEEVE O-RING	RUBBER	1
44	3/4-10 HEX NUT	STAINLESS STEEL	1
44-1	3/4-10 HEX LOCK NUT	STAINLESS STEEL	1
46	HYMAX SHOE	DUCTILE IRON	1
47-1	BONNET RETAINING PIN	STAINLESS STEEL	2
48	STOP PIN	STEEL	1
49	HYMAX GRIP RESTRAINT	SEE PRODUCT SPEC	1
-	HYMAX IDENTIFICATION TAG	PAPER	1
-	ULC LABEL	PAPER	1

4-1/2" CANADA CENTURY
 175 PSI W.P. - 350 PSI TEST.
 WITH HYMAX GRIP RESTRAINT SHOE
 NON-UL/FM APPROVED.
 SEE PRODUCT SPECIFICATION FOR PRESSURE
 RATING OF THE RESTRAINT PER APPLICATION.

AVC (MILLIMETER)	TOLERANCES - MACHINING	THIRD ANGLE PROJECTION
INCH	UNLESS OTHERWISE NOTED	PURCH. FINISH
INITIAL RELEASE	BREAK EDGES FINISH SURFACES	REF. NO. SCALE
DRFT'R ANC 1-15-24	MACH. .006/.016	STK. NO.
CHK'R JBC 2-23-24	125	
APP JBC 2-23-24	FRACTIONS ±1/64	
	DECIMALS 2 PL ±.025	
	3 PL ±.016	
E.O. NUMBER EDS368	MAT'L	REVISION
Mueller Canada	DESCR. CANADA CENTURY ASSEMBLY WITH HYMAX SHOE	NUMBER FH-20042
		SHEET 1 OF 1

FH-20042

REV.	DESCRIPTION	REF.	DRFT'R	CHK'R	APP	DATE