



# INSTA-TITE® 2.0 CONNECTIONS

## Product Specifications

### 1. MATERIAL SPECIFICATIONS

- 1.1 Body – Cast bronze ASTM B594 C89833 or C87850.
- 1.2 Grip Ring – Molded acetal plastic, ASTM D4181. (White for IPS sizes - Red for CTS sizes)
- 1.3 Gasket – EDPM rubber, ASTM D2000.
- 1.4 Grip Ring – 301 Stainless Steel.

### 2. SIZES, OPERATING PRESSURE AND TEMPERATURE

- 2.1 Two basic sizes of connections are available.
  - 2.1.1 CTS polyethylene (PE) tubing per ASTM D-2737 SDR-9. CTS soft K copper tubing per ASTM B88.
  - 2.1.2 IPS polyethylene (PE) pipe per ASTM D-2239 SDR-7. IPS PVC tubing per ASTM D1785.
- 2.2 Operating Pressure – The pressure holding capability of this connection is designed to be greater than that of the valve or fitting on which it is used (only in potable water distribution applications complying with AWWA standards).
- 2.3 Operating temperature range is +32 °F to +100 °F.

### 3. INLET SPECIFICATIONS

- 3.1 Iron pipe threads conform to ANSI B1.20.1.
- 3.2 Copper service threads conform to AWWA Standard C800.
- 3.3 Mueller® multi-purpose end connections attach to a variety of copper water meter yokes in 5/8", 5/8" x 3/4", 3/4", and 1" sizes.

### 4. DESIGN FEATURES

- 4.1 Mueller® INSTA-TITE® Connection has all parts pre-assembled permitting piping to be stabbed into body for fast and easy assembly. Approximately two-inches (2") of pipe insertion depth is provided.
- 4.2 Sealing is provided by an Gasket which will maintain its seal during any longitudinal pipe movement permitted by the design.
- 4.3 Body and grip ring are designed to provide high resistance to pullout which might result from line pressure, back filling, ground settlement, accidental disturbance from ditching equipment, or from changes in pipe due to temperature variation. Proper operation of the connection does permit small amounts of pipe movement within the body which "sets" the grip ring.
- 4.4 If for some reason it becomes necessary to remove the pipe from the connection, a tool is available. Consult installation instructi

***For more information about Mueller or to view our full line of water products, please visit [www.muellercompany.com](http://www.muellercompany.com).  
For customer support or to report any product issues, please call 1.800.423.1323.***

Mueller refers to one or more of Mueller Water Products, Inc. a Delaware corporation ("MWP"), and its subsidiaries. MWP and each of its subsidiaries are legally separate and independent entities when providing products and services. MWP does not provide products or services to third parties. MWP and each of its subsidiaries are liable only for their own acts and omissions and not those of each other. MWP brands include Mueller®, Echologics®, Hydro Gate®, Hydro-Guard®, HYMAX®, i2O®, Jones®, Krausz®, Mi.Net®, Milliken®, Pratt®, Pratt Industrial®, Singer®, and U.S. Pipe Valve & Hydrant. Please see [muellerwp.com/brands](http://muellerwp.com/brands) and [krauszusa.com](http://krauszusa.com) to learn more.

© 2022 Mueller Co., LLC. All Rights Reserved. The trademarks, logos and service marks displayed in this document are the property of Mueller Co., LLC., its affiliates or other third parties. Products above marked with a section symbol (§) are subject to patents or patent applications. For details, visit [www.mwppat.com](http://www.mwppat.com). These products are intended for use in potable water applications. Please contact your Mueller Sales or Customer Service Representative concerning any other application(s).  
F 10112 7/22